

DE LIGHTING INC.

LED High Bay Light



Model	DE-BYB-0-150-XX			DE-BYB-0-200-XX		
Input Voltage	AC100-277V			AC100-277V		
Power (W) ±5%	150W Driver B			200W Driver B		
Beam Angle (degrees)	45°	90°	120°	45°	90°	120°
Luminous Efficiency (lm/w)	83lm/w	92lm/w	95lm/w	80lm/w	92lm/w	92lm/w
Luminous Flux (lm)	12450lm	13800lm	14250lm	16000lm	18400lm	18400lm
Frequency	50/60Hz			50/60Hz		
CCT/Specified	2700K-6500K			2700K-6500K		
CRI	>70 or >80			>70 or >80		
Power Factor	>0.95			>0.95		
LED Chips	San'an/Epistar/Nichia/Cree or specified			San'an/Epistar/Nichia/Cree or specified		
Unit Size(No reflector)	460x460x262mm			460x460x280mm		
Unit Weight(No reflector)	7.3kg			8.5kg		
Size (With reflector)	φ 370mmX572mm(45°)		φ 425mmX476mm(90°)	φ 381X435mm(120°)		
Unit Weight(With reflector)	7.7kg			8.9kg		
Package Size(No reflector)	340*340*330mm/1pcs			340*340*330mm/1pcs		
Gross Weight(No reflector)	8.2kgs			9.4kgs		
Protection Level	IP65			IP65		
working tempt.	-40℃--+50℃			-40℃--+50℃		
Function	Dimmable			Dimmable		
Certificates	ULcUL/FCC			ULcUL/FCC		
Lifespan	30,000 hours			30,000 hours		
Warranty	5 years			5 years		

Driver B:Meanwell brand