

DE LIGHTING INC.

LED Street Light



Model	DE-SLD-2-080M-XX		DE-SLD-3-120M-XX		DE-SLD-4-160M-XX	
Input Voltage	AC100-277V					
Power (W) ±5%	80W DriverA	90W DriverB	120W DriverA	135W Driver B	160W DriverA	180W Driver B
Frequency	50/60Hz					
CCT/Specified	2700K-6500K					
CRI	>70 or >80					
Luminous Efficiency (lm/w)	106lm/w	110lm/w	115lm/w	120lm/w	125lm/w	125lm/w
Luminous Flux (lm)	8480lm	9900lm	13800lm	16200lm	20000lm	22500lm
Beam Angle (degrees)	155° /80°					
Power Factor	≥0.95					
LED Chips	Epistar/Philips/Cree or specified					
Unit Size (mm)	613*340.5*183.5mm		706*340.5*183.5mm		798*340.5*183.5mm	
Package Size	720*435*290mm/1pcs		810*435*290mm/1pcs		900*435*290mm/1pcs	
Unit Weight	9.65kg		10.75kg		13.4kg	
Gross Weight	11.4kg		12.5kg		15.3kg	
Protection Level	IP66					
Working temperature	-40℃--+50℃					
Function	Dimmable					
Certificates	ULcUL/DLC/FCC					
Lifespan	30,000 hours					
	5 years		5 years		5 years	